ELSEVIER

Wear 206 (1997) 251

WEAR

Author Index of Volume 206

Afaghani, J.E.D., 221
Arumugam, P., 122
Azarkhin, A., 147

Bokiy, Yu.F., 214
Bonneau, O., 244
Bouzakis, K.-D., 197

Cao, Z.Y., 83
Çavdar, B., 15
Chandrasekaran, M., 1
Chang, L., 113

Dama, R., 113
Devenpeck, M.L., 147
Dosbayeva, G.K., 214

Fang, L., 87
Fishkis, M., 156
Fox-Rabinovich, G.S., 214
Frêne, J., 244

Gao, Y.-M., 87
Goh, G.K.L., 24

Hamblin, M.G., 69
Ho, K.-C., 60
Hu, J.D., 83

Ivanyk, E., 53

Jeng, M.-C., 60

Kashiwaya, S., 8
Kovalev, A.I., 214
Kumar, A., 130
Kuroda, S., 230, 238

Lim, L.C., 24
Lim, S.C., 24
Lin, J.C., 156
Lin, J.-R., 171
Liu, J., 76
Liu, Y.B., 83
Luo, Z., 76

Ma, M.-T., 100
Maleque, M.A., 179
Masjuki, H.H., 179

Miao, H., 76
Mishina, V.P., 214
Moslehy, F.A., 136

Nakamoto, T., 221

Ovaert, T.C., 94

Podsiadlo, P., 39
Prabhu, B.S., 122

Rahman, M., 24
Ramachandra, S., 94
Ravikiran, A., 33
Rice, S.L., 136
Rohatgi, P.K., 83

Schmid, S.R., 130
Shuster, L.Sh., 214
Singh, P., 1
Skeldon, P., 187
Stachowiak, G.W., 39, 69
Su, J.-Y., 87
Surappa, M.K., 33
Swarnamani, S., 122

Takahashi, N., 8
Tevruz, T., 204
Thompson, G.E., 187

Vidakis, N., 197

Wainstein, D.L., 214
Wang, H.W., 187
Wilson, W.R.D., 130

Xie, Z.-G., 87

Yamaguchi, K., 221
Yan, S., 230, 238
Yevtushenko, A., 53
Yoshino, K., 221

Zhao, X., 76
Zhu, B., 76

Elsevier Science S.A.

ELSEVIER

Wear 206 (1997) 253–256

WEAR

Subject Index of Volume 206

Abrasive wear
characterisation of surface abrasivity and its relation to two-body abrasive wear, 69
Abrasivity
characterisation of surface abrasivity and its relation to two-body abrasive wear, 69
Accuracy
an efficient and accurate calculation of traction in elastohydrodynamic contacts, 113
Active control
non-linear behavior of a flexible shaft partly supported by a squeeze film damper, 244
Additive effects
effect of temperature, substrate type, additive and humidity on the boundary lubrication in a linear perfluoropolyalkylether fluid, 15
Adhesive wear
tribological characteristics of Si_3N_4 ceramic sliding on stainless steel, 76
Alloying
characteristic features of alloying HSS-based deformed compound powder materials with consideration for tool self-organization at cutting. 1. Characteristic features of wear in HSS-based deformed compound powder materials at cutting, 214
Alumina
effect of grain size on wear behaviour of alumina cutting tools, 24
Aluminium
formation and characterization of self-lubricating MoS_2 precursor films on anodized aluminium, 187
Aluminum matrix composite
wear resistance of laser processed Al–Si–graphite$_p$ composites, 83
Angularity
characterisation of surface abrasivity and its relation to two-body abrasive wear, 69
Anodizing
formation and characterization of self-lubricating MoS_2 precursor films on anodized aluminium, 187
Antifriction
sintered iron-based antifriction materials with added β-SiC, 1

Bearing materials
effect of temperature, substrate type, additive and humidity on the boundary lubrication in a linear perfluoropolyalkylether fluid, 15
Boundary lubrication
effect of temperature, substrate type, additive and humidity on the boundary lubrication in a linear perfluoropolyalkylether fluid, 15
Braking
determination of temperatures for sliding contact with applications for braking systems, 53
Braking time
determination of temperatures for sliding contact with applications for braking systems, 53

Ceramic cutting tools
effect of grain size on wear behaviour of alumina cutting tools, 24
Composites
tribological characteristics of short glass fibre reinforced polycarbonate composites, 60
Contact area
determination of temperatures for sliding contact with applications for braking systems, 53
Continuum mechanics
lubrication with emulsion: first report, the extended Reynolds equation, 230
Couple stress fluids
effects of couple stresses on the lubrication of finite journal bearings, 171
Cutting
tear-off wear mechanism of sintered diamond tool in cutting SiC-particle-strengthened epoxy composites, 221
Cutting tools
characteristic features of alloying HSS-based deformed compound powder materials with consideration for tool self-organization at cutting. 1. Characteristic features of wear in HSS-based deformed compound powder materials at cutting, 214

Damping coefficient
effects of journal misalignment on the performance characteristics of three-lobe bearings, 122
Dispersion-strengthened composite
tear-off wear mechanism of sintered diamond tool in cutting SiC-particle-strengthened epoxy composites, 221
Dynamic behavior
modeling friction and wear phenomena, 136

Effect of grain size
effect of grain size on wear behaviour of alumina cutting tools, 24
Efficiency
an efficient and accurate calculation of traction in elastohydrodynamic contacts, 113
Elastohydrodynamics
an expedient approach to the non-newtonian thermal EHL in heavily loaded point contacts, 100
Electrorheological fluid
non-linear behavior of a flexible shaft partly supported by a squeeze film damper, 244
Emulsion
lubrication with emulsion: first report, the extended Reynolds equation, 230
lubrication with emulsion. II. The viscosity coefficients of emulsions, 238
Emulsions
particle behavior in two-phased lubrication, 130
Extended Reynolds equation
lubrication with emulsion: first report, the extended Reynolds equation, 230

lubrication with emulsion. II. The viscosity coefficients of emulsions, 238

FEM simulation
prediction of the fatigue behaviour of physically vapour deposited coatings in the ball-on-rod rolling contact fatigue test, using an elastic–plastic finite elements method simulation, 197
Fibre orientation
tribological characteristics of short glass fibre reinforced polycarbonate composites, 60
Finite journal bearings
effects of couple stresses on the lubrication of finite journal bearings, 171
Flash temperature parameter
investigation of the anti-wear characteristics of palm oil methyl ester using a four-ball tribometer test, 179
Flexible shaft
non-linear behavior of a flexible shaft partly supported by a squeeze film damper, 244
Fluid bearing
non-linear behavior of a flexible shaft partly supported by a squeeze film damper, 244
Four-ball machine
investigation of the anti-wear characteristics of palm oil methyl ester using a four-ball tribometer test, 179
Friction
effects of journal misalignment on the performance characteristics of three-lobe bearings, 122
enhanced model of a plowing asperity, 147
Frictional heating
determination of temperatures for sliding contact with applications for braking systems, 53
Friction and wear
investigation on the components and the formation of a tribochemical film in the Si_3N_4–gray iron sliding pair lubricated with distilled water, 87
Friction control
characteristic features of alloying HSS-based deformed compound powder materials with consideration for tool self-organization at cutting. 1. Characteristic features of wear in HSS-based deformed compound powder materials at cutting, 214

Gears
experiments of scoring and the calculation of scoring on gears by heat method, 204
Graphite
investigation on the components and the formation of a tribochemical film in the Si_3N_4–gray iron sliding pair lubricated with distilled water, 87
Graphite particle
wear resistance of laser processed Al–Si–graphite$_p$ composites, 83
Gray cast iron
investigation on the components and the formation of a tribochemical film in the Si_3N_4–gray iron sliding pair lubricated with distilled water, 87

Heavy loads
an expedient approach to the non-newtonian thermal EHL in heavily loaded point contacts, 100
HRTEM
high resolution transmission electron microscopy observation of the MoS_2–Au interface formed due to stick–slip of MoS_2 sliding on Au in relation to the friction trace, 8
HSS-based compound powder material
characteristic features of alloying HSS-based deformed compound powder materials with consideration for tool self-organization at cutting. 1. Characteristic features of wear in HSS-based deformed compound powder materials at cutting, 214
Humidity
effect of temperature, substrate type, additive and humidity on the boundary lubrication in a linear perfluoropolyalkylether fluid, 15

Injection moulding
tribological characteristics of short glass fibre reinforced polycarbonate composites, 60
Iron
sintered iron-based antifriction materials with added β-SiC, 1

Journal bearing
effects of journal misalignment on the performance characteristics of three-lobe bearings, 122

Laser processing
wear resistance of laser processed Al–Si–graphite$_p$ composites, 83
Lubrication
tribological characteristics of Si_3N_4 ceramic sliding on stainless steel, 76
an expedient approach to the non-newtonian thermal EHL in heavily loaded point contacts, 100
particle behavior in two-phased lubrication, 130
lubrication with emulsion: first report, the extended Reynolds equation, 230
Lubrication performance
effects of couple stresses on the lubrication of finite journal bearings, 171

Metalworking
formation and evolution of a subsurface layer in a metalworking process, 156
Misalignment
effects of journal misalignment on the performance characteristics of three-lobe bearings, 122
Mixture
lubrication with emulsion: first report, the extended Reynolds equation, 230
MMC
effect of sliding speed on wear behaviour of A356 Al-30 wt.% SiC$_p$ MMC, 33
Modeling
modeling friction and wear phenomena, 136
Molybdenum disulphide
formation and characterization of self-lubricating MoS_2 precursor films on anodized aluminium, 187
MoS_2–Au
high resolution transmission electron microscopy observation of the MoS_2–Au interface formed due to stick–slip of MoS_2 sliding on Au in relation to the friction trace, 8

Non-linear behavior
non-linear behavior of a flexible shaft partly supported by a squeeze film damper, 244
Non-newtonian lubricants
an expedient approach to the non-newtonian thermal EHL in heavily loaded point contacts, 100

Oil concentration
lubrication with emulsion. II. The viscosity coefficients of emulsions, 238
Oscillations in friction
effect of sliding speed on wear behaviour of A356 Al-30 wt.% SiC$_p$ MMC, 33

Palm oil methyl ester
investigation of the anti-wear characteristics of palm oil methyl ester using a four-ball tribometer test, 179
Particles
particle behavior in two-phased lubrication, 130
Plastic composite
tear-off wear mechanism of sintered diamond tool in cutting SiC-particle-strengthened epoxy composites, 221
Plowing
enhanced model of a plowing asperity, 147
Point contacts
an expedient approach to the non-newtonian thermal EHL in heavily loaded point contacts, 100
Polymer
the effect of controlled surface topographical features on the unlubricated transfer and wear of PEEK, 94
Powder metallurgy
sintered iron-based antifriction materials with added β-SiC, 1
PVD coatings
prediction of the fatigue behaviour of physically vapour deposited coatings in the ball-on-rod rolling contact fatigue test, using an elastic–plastic finite elements method simulation, 197

Robustness
an efficient and accurate calculation of traction in elastohydrodynamic contacts, 113
Rolling contact fatigue
prediction of the fatigue behaviour of physically vapour deposited coatings in the ball-on-rod rolling contact fatigue test, using an elastic–plastic finite elements method simulation, 197
Roughness
the effect of controlled surface topographical features on the unlubricated transfer and wear of PEEK, 94

Scanning electron microscopy
characterization of surface topography of wear particles by SEM stereoscopy, 39
Scoring
experiments of scoring and the calculation of scoring on gears by heat method, 204
Scoring on gears
experiments of scoring and the calculation of scoring on gears by heat method, 204
Scribing
the effect of controlled surface topographical features on the unlubricated transfer and wear of PEEK, 94
Secondary structures
characteristic features of alloying HSS-based deformed compound powder materials with consideration for tool self-organization at cutting. 1. Characteristic features of wear in HSS-based deformed compound powder materials at cutting, 214
Self-organization
characteristic features of alloying HSS-based deformed compound powder materials with consideration for tool self-organization at cutting. 1. Characteristic features of wear in HSS-based deformed compound powder materials at cutting, 214
Silicon carbide
sintered iron-based antifriction materials with added β-SiC, 1
Silicon carbide particle
tear-off wear mechanism of sintered diamond tool in cutting SiC-particle-strengthened epoxy composites, 221
Silicon nitride
tribological characteristics of Si_3N_4 ceramic sliding on stainless steel, 76
investigation on the components and the formation of a tribochemical film in the Si_3N_4–gray iron sliding pair lubricated with distilled water, 87
Sintered diamond tool
tear-off wear mechanism of sintered diamond tool in cutting SiC-particle-strengthened epoxy composites, 221
Sintering
sintered iron-based antifriction materials with added β-SiC, 1
Slurries
particle behavior in two-phased lubrication, 130
Speed
effect of sliding speed on wear behaviour of A356 Al-30 wt.% SiC_p MMC, 33
Squeeze film damper
non-linear behavior of a flexible shaft partly supported by a squeeze film damper, 244
Stacking fault
high resolution transmission electron microscopy observation of the MoS_2–Au interface formed due to stick–slip of MoS_2 sliding on Au in relation to the friction trace, 8
Stainless steel
tribological characteristics of Si_3N_4 ceramic sliding on stainless steel, 76
Static characteristics
effects of couple stresses on the lubrication of finite journal bearings, 171
Stereoscopic matching
characterization of surface topography of wear particles by SEM stereoscopy, 39
Stereoscopy
characterization of surface topography of wear particles by SEM stereoscopy, 39
Stick–slip
high resolution transmission electron microscopy observation of the MoS_2–Au interface formed due to stick–slip of MoS_2 sliding on Au in relation to the friction trace, 8
Stiffness
effects of journal misalignment on the performance characteristics of three-lobe bearings, 122
Subsurface layer
formation and evolution of a subsurface layer in a metalworking process, 156
Surface characterisation
characterisation of surface abrasivity and its relation to two-body abrasive wear, 69
Surface films
effect of temperature, substrate type, additive and humidity on the boundary lubrication in a linear perfluoropolyalkylether fluid, 15
Surface topography
characterization of surface topography of wear particles by SEM stereoscopy, 39
the effect of controlled surface topographical features on the unlubricated transfer and wear of PEEK, 94
Suspensions
particle behavior in two-phased lubrication, 130
Synthetic lubricants
effect of temperature, substrate type, additive and humidity on the boundary lubrication in a linear perfluoropolyalkylether fluid, 15

Tear-off mechanism
tear-off wear mechanism of sintered diamond tool in cutting SiC-particle-strengthened epoxy composites, 221
Temperature field
determination of temperatures for sliding contact with applications for braking systems, 53
Thermal effects
effect of temperature, substrate type, additive and humidity on the boundary lubrication in a linear perfluoropolyalkylether fluid, 15
an expedient approach to the non-newtonian thermal EHL in heavily loaded point contacts, 100

Thermal elastohydrodynamics
an efficient and accurate calculation of traction in elastohydrodynamic contacts, 113
Tool wear
tear-off wear mechanism of sintered diamond tool in cutting SiC-particle-strengthened epoxy composites, 221
Traction
an efficient and accurate calculation of traction in elastohydrodynamic contacts, 113
Tribochemical reaction
investigation on the components and the formation of a tribochemical film in the Si_3N_4–gray iron sliding pair lubricated with distilled water, 87
Tribofilm
investigation on the components and the formation of a tribochemical film in the Si_3N_4–gray iron sliding pair lubricated with distilled water, 87
Tribology
particle behavior in two-phased lubrication, 130
Tribosystems
modeling friction and wear phenomena, 136

Unlubricated sliding
modeling friction and wear phenomena, 136
Upper bound method
enhanced model of a plowing asperity, 147

Viscosity coefficients
lubrication with emulsion. II. The viscosity coefficients of emulsions, 238

Wear
sintered iron-based antifriction materials with added β-SiC, 1
effect of temperature, substrate type, additive and humidity on the boundary lubrication in a linear perfluoropolyalkylether fluid, 15
effect of sliding speed on wear behaviour of A356 Al-30 wt.% SiC_p MMC, 33
investigation of the anti-wear characteristics of palm oil methyl ester using a four-ball tribometer test, 179
Wear mechanisms
effect of grain size on wear behaviour of alumina cutting tools, 24
Wear particles
characterization of surface topography of wear particles by SEM stereoscopy, 39
Wear resistance
wear resistance of laser processed Al–Si–graphite$_p$ composites, 83
Wear transfer film
the effect of controlled surface topographical features on the unlubricated transfer and wear of PEEK, 94